REPOI	RT DOCU	MENTAT	ON PAGE	Form Approved OMB No. 0704-0188							
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing this collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Department of Defense, Washington Headquarters Services, Directorate for Information Operations and Reports (0704-0188), 1215 Lefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302. Respondents should be aware that notwithstanding any other provision of law, no person shall be subject to any penalty for failing to comply with a collection of information if it does not display a currently valid OMB control number. PLEASE DO NOT RETURN YOUR FORM TO THE ABOVE ADDRESS.											
1. REPORT D	ATE	2. REPORT To Professional pa	YPE	3. DATES COV							
4. TITLE AND		Trovostona pe		5a. CONTRACT NUMBER							
Head and Ne Rotary Wing +		oments Developed	during Tactical and	5b. GRANT NUMBER							
, , , ,				5c. PROGRAM ELEMENT NUMBER							
6. AUTHOR(S	3)			5d. PROJECT NUMBER							
Barry Shender Wayne Isdahl	Glenn Paskoff; Gr	eg Askew; Rich Co	ughlan;	5e. TASK NUMBER							
				5f. WORK UNIT NUMBER							
7. PERFORM	NG ORGANIZAT	ON NAME(S) AN	D ADDRESS(ES)	8. PERFORMING ORGANIZATION REPORT NUMBER							
22347 Cedar P	fare Center Aircraf Point Road, Unit #6 Maryland 20670-		•		·						
	NG/MONITORING	G AGENCY NAME	(S) AND	10. SPONSOR/MONITOR'S ACRONYM(S)							
				11. SPONSOR/MONITOR'S REPORT NUMBER(S)							
12. DISTRIBUTION/AVAILABILITY STATEMENT											
		ibution is unlimited	· · · · · · · · · · · · · · · · · · ·								
13. SUPPLEM	ENTARY NOTES										
14. ABSTRAC	T T										
Neck injury risk may increase when aircrew wear head-mounted equipment during flight; however, maneuvering acceleration head/neck forces and moments have not been determined.											
15. SUBJECT TERMS											
16. SECURIT	Y CLASSIFICATIO	ON OF:	17. LIMITATION OF ABSTRACT	18. NUMBER OF PAGES	19a. NAME OF RESPONSIBLE PERSON Barry Shender						
a. REPORT b. ABSTRACT c. THIS PAGE		c. THIS PAGE	OI ADDINACI	01111010	19b. TELEPHONE NUMBER (include area						
Unclassified	Unclassified	Unclassified	SAR	1	code) (301) 342-8881						

Standard Form 298 (Rev. 8-98) Prescribed by ANSI Std. Z39-18

HEAD AND NECK LOADS AND MOMENTS DEVELOPED DURING TACTICAL AND ROTARY WING +Gz-STRESS

B. S. Shender*, G. Paskoff, G. K. Askew, R. Coughlan, and W. Isdahl. NAWCAD Patuxent River, MD; AFRL/HEPM, Brooks AFB, San Antonio, TX.

Purpose. Neck injury risk may increase when aircrew wear head-mounted equipment during flight, however, maneuvering acceleration head/neck forces and moments have not been determined. Methods. Added weight and varying center-of-gravity (CG) effects were determined using an instrumented manikin at the Brooks centrifuge. A custom designed aluminum head fixture was developed to support the weights. A solid aluminum neck was used to prevent excess unrealistic head motion seen in previous studies. Data included centrifuge Gz, head acceleration (3 axes), head and C7-T1 point moment (My), compressive (Fz) and shear (Fx) forces. +Gz profiles (5s plateau) simulated helicopter (0.5G/s to +1.75 or +4Gz) and tactical aircraft capabilities (2G/s or 6G/s to +4,6,8,10,12 Gz). Two Gillingham simulated aerial combat maneuvers (SACM) (alternating plateaus with either +6Gz or +10Gz peak) were included. Impact of weight (3.5 to 6lb.), weight position (forward pitch and lateral planes), and onset rate were determined using ANOVA with a Fisher's LDS post-hoc test. Seven military helmet systems were also tested. Results. Head (H) and neck (N) forces, accelerations, and moments increased with increasing +Gz-load, weight and onset rate (p<0.01). Weights positioned laterally led to lower forces and moments when compared to forward pitch locations (Table I). SACM HGx, HGy, HFx, HMy and NMy differed from comparable 5s plateau values for all configurations, possibly due to more realistic motion effects. Conclusions. Effects of CG and +Gz-stress on head/neck loads and moments have been quantified.

TABLE I. Mean ± 1 sd NMy (in-lb.) and resultant neck force during plateau at 2G/s.

		NMy		NFxz	
Configuration	Weight (lb.)	+4Gz	+12Gz	+4Gz	+12Gz
Lateral	4.0	160±1	690±2	62±0.2	230±0.2
Lateral	5.5	177±1	752±2	70 ± 0.1	250±0.2
60° pitch	4.0	181±1	768±2	65±0.1	233±0.2
60° pitch	5.5	245±1	987±2	71±0.2	250±0.2
Navy-T	3.0	177±1	736±2	64±0.1	228±0.2
Air Force-T	3.3	177±1	726±2	64 ± 0.1	227±0.2
Navy-TDN	5.4	198±1	809±2	71±0.2	248±0.2
J-D	4.1	203±1	841±2	64±0.3	234±0.2

Helmet systems: T: tactical; DN: day/night with optics; J-D: prototype joint service display.